

06.0052

DOLPHIN SURFACE MOUNTED SOAP DISPENSER

- › Surface Mounted Soap Dispenser
- › Wall mounted, satin or polished stainless steel finishes soap dispenser; 600ml capacity
- › Usage: Low Traffic Areas

| | |
|------------|--------|
| DIAMETER | 76 MM |
| HEIGHT | 216 MM |
| PROJECTION | 110 MM |

SPECIFICATION

Wall mounted liquid soap dispenser: 06.0052 satin or 06.0053 polished stainless steel with acrylic removable lid for filling, 600ml capacity.
Manufactured by Dolphin Solutions Ltd.

PRODUCT CODES

| | |
|----------------------------|---------|
| › Satin stainless steel | 06.0052 |
| › Polished stainless steel | 06.0053 |


MATERIAL

- › Cylinder: 1.5mm stainless steel grade 1.4401 (316)
- › Lid: Acrylic
- › Internal Wall Mounts: Brass CW614N
- › Approximate unit weight: 1.4kg

INSTALLATION

See diagram opposite

- › Mark location of fixing holes on wall.
- › Loosen grub screws (C) with the hexagon key until brass-mounting tubes (D) fall free.
- › Align the brass mounting tubes with the fixing holes in the wall and secure using suitable screws (Please check the screws supplied are suitable for the installation).
- › Position the cylinder body (E) over the brass mounting tubes and secure by tightening the grub screws.
- › Remove lid (A) (Remove white protective cover from lid on install) and fill the soap dispenser to just below the vent hole (B).
- › For best results always use Dolphin solutions ltd 'Pearlised' liquid soap (part No. 06.8305)
- › Fit the lid back into position ensuring that it is securely in place.
- › Do not open the dispenser from the base without seeking advice from the manufacturer:



OPERATION

- › Push lower ring horizontally towards the wall to dispense liquid soap into palm of hand. Each stroke delivers approximately 1ml of liquid soap per activation. Recommended for light to medium use areas.
- › Fill soap dispenser by removing acrylic lid and pouring liquid soap into container. To purge, press lower ring until soap begins to dispense from nozzle.

Liquid Soap

- › We recommend using Dolphin solutions ltd 'Pearlised' liquid soap (Product code 06.8305). We do not recommend using high viscosity liquid soaps or gels, which may impair function. Warning: Liquid soap with high sodium chloride content can cause corrosion and may invalidate the product warranty

INSTALLATION KIT

See diagram above

- › 1 x Stainless steel soap dispensing cylinder
- › 1 x Round tinted acrylic lid with fitted 'O' ring
- › 2 x Brass wall mounting tubes
- › 2 x Grub screws
- › 2 x No.10 fixing screws
- › 2 x Wall plugs
- › 1 x Hexagon key
- › A. See through lid
- › B. Vent hole
- › C. Grub screw (2)
- › D. Brass wall mounting tube (2)
- › E. Stainless steel cylindrical body

CARE AND MAINTENANCE

- › If dispenser fails to function, empty the liquid soap from the container and re-fill with warm water. Pump the warm water through the dispenser to dislodge any dried soap residue and then re-fill the container with fresh liquid soap.
- › Use a stainless steel cleaner. Never use an abrasive cloth to remove stubborn stains. Dry with a soft clean cloth.

THIS PRODUCT FALLS WITHIN THE SCOPE OF THE WASTE ELECTRICAL & ELECTRONIC EQUIPMENT REGULATIONS DIRECTIVE (WEEE)

This product should not be disposed of with household waste. Please recycle where facilities exist or contact Dolphin Solutions Ltd for further assistance. Check with your local authority for further recycling advice.



WARRANTY

This product is covered by a 12-month warranty from the date of purchase to be free from defects if installed and maintained in accordance with these instructions. Dolphin Solutions will replace or repair (as appropriate) free of charge any product with a proven manufacturing defect if reported within the warranty period.

Dolphin Solutions Ltd reserves the right to amend the design or dimensions without formal notice.