



DB250 / DB275

DOLPHIN ELECTRONIC INFRARED TAP WITH TEMPERATURE ADJUSTMENT LEVER

- > Touch Free Tap – for ultimate hygiene – prevents cross contamination
- > Polished chrome plating
- > Water Supply: hot and cold supply featuring temperature adjustment lever
- > Flow rate – 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates available to special order – please enquire)
- > Flow time once user's hands are removed from the tap - 1 second (adjustable by using remove control DB51)
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > Tap settings may be adjusted by using remote control (DB51)
- > Mandatory Hygiene Flush feature can be specified to combat Legionella
- > WRAS approved
- > 2 year manufacturer's warranty
- > Power connections: tap: male / power source: female
- > Complies with SKA rating criteria
- > The two flexible connectors contain integral check (non-return) valves
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this Dolphin Blue tap
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT 1 credits.

HEIGHT	142 MM
DIAMETER	50 MM
PROJECTION	60 MM

- > Power Source: 9 Battery / Plug-in 9 Volt transformers
- > Power connections: tap: male / power source: female
- > 3/8" BSP water supply connector
- > Maximum water temperature 70°C
- > Operating pressure 0.5 - 8.0 bar (7 - 116 PSI)
- > Min-Max thickness: 2-27mm
- > Counter Hole: diameter 28-34mm
- > Minimum/maximum thickness: 2-27mm

PRODUCT CODES

BATTERY POWERED

- > Same product in polished chrome **DB250C**
- > Same product in brushed nickel plating **DB250S**

TRANSFORMER POWERED

- > Same product in polished chrome **DB275C**
- > Same product in brushed nickel plating **DB275S**