





DBL250 / DBL275

DOLPHIN COUNTER MOUNTED ELECTRONIC INFRARED TAP WITH TEMPERATURE ADJUSTMENT LEVER

> WRAS Approved product

- > Touch Free Electronic Tap Tap is activated when the user brings hands within the State of the art electronic infrared sensor's range
- > Ultimate Hygiene Prevents cross contamination. Ideal for counter top basins
- > Flow time once user's hands are removed from the tap I second (adjustable by using remove control DB51)
- > Flow rate 3.8 litres/minute with our standard fitted flow regulator at any pressure between 0 and 6 bar (other flow rates such as 1.89 and 1.33 LPM available to special order – please enquire)
- > Quality polished or brushed chrome plated brass finishes available
- > Tap settings may be adjusted by using remote control (DB50)
- > Filters, fixing bolts, installation instructions and power source supplied with each
- > WRAS approved
- > 2 year manufacturer's warranty
- > Mandatory Hygiene Flush is available can be set to 12,24 or 48 Hour intervals optional extra & must be specified when ordering
- > Complies with SKA rating criteria
- > The two flexible connectors contain integral check (non-return) valves
- > Interchangeable STD M22/24 Neoperl Aerator insert
- > We recommend our Dolphin Blue DB61 TMV3 be used in conjunction with this Dolphin Blue tap
- > Our low flow taps are fully BREEAM compliant and contribute to up to five BREEAM WAT | credits.

 HEIGHT
 338 mm

 DIAMETER
 44 mm

 PROJECTION
 104 mm

- > Power Source: 9 Volt Battery (features low battery warning) / Plug-in 9 Volt transformers (supplied)
- Water Supply: hot and cold supply featuring temperature adjustment lever
- > 3/8" BSP Water supply connection
- > Operating pressure 0.5 8.0 bar (7 116 PSI)
- > Maximum water temperature 70°C
- > Water Supply : Hot and Cold
- > Counter: Hole : diameter 34-36mm
- > Min-Max thickness : 2-27mm

PRODUCT CODES

BATTERY POWERED

Polished Chrome Plate
 Brushed (Satin) Chrome Plate
 DBL250C
 DBL250S-2

TRANSFORMER POWERED

Polished Chrome Plate
 Brushed (Satin) Chrome Plate
 DBL275C
 DBL275S-2

TECHNICAL HELPLINE 01424 202224 DOLPHINSOLUTIONS.CO.UK